

## Subdecay Studios – Anamnesis Echo

### Modulated Delay

The Anamnesis Echo is hand crafted in Oregon with high quality components. Thank you for purchasing a Subdecay pedal.

### What is the Anamnesis all about?

This pedal is a modulated echo effect with ~ 600ms of max delay time. It's best suited for creating lush walls of modulated swirling delay sounds. The modulation speed is capable of up to 30hz, which can make for some very creepy sounds. Natural trails are possible too when the pedal is bypassed.

### Controls:

**Level:** This control affects the echo signal volume only. The dry signal remains at 100%.

**Time:** Adjusts the delay time from ~60ms to ~600ms.

**Regen:** Controls the amount of feedback from the delay output back to the input. Increases the number of repeats as the knob is turned to the right.

**Modulation – Speed:** Controls the LFO rate that modulates the delay time.

**Modulation – Depth:** Controls how much the delay time is modulated by the LFO. Turn all the way to the left for zero modulation.

### Internal switch:

**Trails:** Turns on or off the natural trails option. When on, repeats will continue with the pedal in bypass.

### Setting ideas:

**Chorus:** Set the time and regen to minimum. Use the speed and depth control to create a chorus effect.

**X-COM:** Set the delay time to about 9:00. Regen at 12:00. Speed and depth to 3:00 or higher to get creepy 90's video game sounds.

**Pitch Chaos:** Turn the delay time down low, and the repeats modulation depth up high. It can get pretty messy.

### Power:

The Anamnesis is powered by a dedicated Class II regulated 9 to 18 volt power supply with a negative center 2.1mm barrel plug. Current draw under normal operation is less than 100mA.

If using a “daisy chain” power supply all other units on the power supply MUST be negative ground.

### Specifications:

Input impedance: 2M

Output impedance: Less than 1K

### Operation and care:

Keep away from extreme heat, cold and moisture. Use only a dry towel to clean. No user serviceable parts. Contact Subdecay Studios for repair or maintenance.

### Warranty:

Subdecay Studios offers a 3 year limited warranty from the purchase date to the original purchaser. This warranty does not cover misuse, or the neglect of the user. It also does not cover the finish, paint, or any external superficial damage. Any unauthorized repairs or modifications will void the warranty. Subdecay Studios, Inc. assumes no liability for this product.

V 1.00A

## USER GUIDE



Subdecay Studios, Inc.

503 538 3632

support@subdecay.com

More information available at [www.subdecay.com](http://www.subdecay.com)



This Document was believed to be accurate at the time it was created.  
Specifications are subject to change without notice.

SUBDECAY STUDIOS INC.

©2012